

WAVEPOS 50

All-in-one POS Terminal Solution



- Intel Duo Core Processors
- Compact design
- Flexible Installation with Expandability
- Cost effective solution
- Versatile Combination
- Industrial circuit and components designed



Total Solution



Multi-Adjustable Angles



Customer Display VFD Type



CF Card Extension



Wall Mount Design.



Price Checker.

System	
CPU Support	Intel ATOM Dual Core D525 1.8Ghz CPU Intel Core 2 Duo 1.83G T5600 Intel IVY Bridge Intel® Core i5/i3 Dual Cores CPU
Memory	Support up to 4GB DDR3
Core Logic	Intel NM10 / 945GM / HM76
Network	10/100/1000 Base-T Fast Ethernet
Power Supply	12V Power Adaptor
System weight	8.5 kgs
Dimension (WxHxD)	320 x350 x 250mm
O/S Compliant	Windows XP/XPE, WEPOS, POSReady 2009, Win 7, Win8 (Ivy platform only)
Storage	
HDD	1 x 2.5" SATA HDD
SSD	MLC SATA interface 16GB/32GB/64GB
I/O Ports	
USB	7 ports, 3 internal (one reserved for touch screen) and 4 external.
Serial Ports	6 x COM (w/ +5V, +12V selectable), 2 internal and 4 external.
PS/2	1 x PS/2 keyboard port
LAN	1 x 10/100/1000 Mbps (RJ45)
VGA	1 x DB-15 VGA Interface
Parallel	1xDB25
Audio	AC'97 Codec Audio
Cash Drawer	1xRJ11
DC-IN	12V DC-IN
Power Switch	1 x Power Switch
Display	
LCD	15" TFT LCD Panel
Max. Resolution	1024 x 768
Brightness	250 nits
Touch Screen	5 Wire resistive touch panel
Peripheral Options	
Printer	TP-260
Customer Display	VFD Type: 20 columns x 2 lines, each column 5x7 dots LCD Type: 8" or 10" LCD
MSR	JIS-I or II, ISO Track 1/2/3 USB (default)
i-button	Read only, USB interface
Color	Dark Grey
Fingerprint	Fingerprint module (USB HID interface)
RFID	ISO 14443A, UltraLight, Mifare@PRO, DESfire