

WiFi SIP Phone IPP-155

PRODUCT DATA



- WiFi SIP Phone
- 802.11b/g
- 1.44" LCD , 65K color CSTN , 128*128
- 130*48*18 mm , 110g
- Internal antenna
- Standby time 160hr
- Talk time 6hr
- Langue : English/Chinese
- Support Hand-free mode
- Phonebook 200 records
- 4 sets SIP profile
- Wallpaper supper JPEG , BMP
- G.711(a/u-law), G729a/b
- WEP 64, WEP 128, WPA-PSK, WPA2-PSK
- FTP firmware upgrade

With benefit of VoIP and WiFi , this WiFi Phone enable user to enjoy the VoIP service without extra equipment. Clear voice and high sensitivity of the WiFi access which make people call VoIP just like cell phone or cordless phone. Simple setup and long standby time which is the best choice of VoIP CPE devices

WiFi SIP Phone

Feature

- Langue : English / Chinese
- Wallpaper support JPEG and BMP format
- IETF SIPv2 (RFC3261)
- Operation mode 802.11b/g
- Call history :
Dialed call Missed call,
Received call, Call duration
- Call Feature:
Call hold, Call mute, Call waiting, Call transfer, Call forward,
- Support Hand-free mode
- G.711(a/u-law), G.729a/b, CNG, PLC, AEC, VAD,
- Adaptive jitter buffer
- SIP profile 4 set
- MD5 for SIP authentication (RFC2069/RFC2617)
- Ringtone support 6-chords polyphonic midi and MP3
- Protocols :
TCP,UDP,IP,DHCP,RTP,
RTCP,ICMP,HTTP,SNTP,TFTP,DNS,
ARP/RARP
- Phone book support Speed dial and group
- Layer 2 intelligent roaming algorithm, WMM/WMM-PS
- WiFi Security: WEP 64, WEP 128,
- WPA-PSK, WPA2-PSK(TKIP & AES)
- Support outbound proxy
- IP Support: Static IP,DHCP
- In-band / Out-of-band DTMF (RFC2833) / SIP INFO
- Support FTP firmware upgrade

Specification

- Form Factory: Bar Type
- Phone Book 200 Records
- Support vibrator
- 24 Keypads
- Standard 5pin mini USB IO connector
- Display 1.44" LCD
- Standby time 160 hr
- Talk time 6 hr
- Support USB Charge
- Battery capacity 1000mAh
- Charge time 3 hr
- Memory:
NOR Flash 8MB
SRAM: 4MB
- Adapter:
Input 100~240V 50~60Hz
Output 5V 1.2A

Environment

- Dimension:
130H x 48W x 18T mm
- Weight: 200g
- Environmental
Operating temperature: 0~40°C
Storage temperature: 10~60°C
Operating humidity: 10%~90%
- Certification Compliance
FCC Part 15 Class B
CE Class B
EN60950

Date: 20101130

Ordering Information:

Model : IPP-155

Distributor: